



MIDDLE MOUNT II

FOR FILM & VIDEO

STABILIZATION: BRUTE GRYOS
POINT-OF-VIEW: SIDE (LEFT OR RIGHT)
MOVEMENT: PAN, TILT & ROLL (100°)

FOCAL RANGE: 18-250MM
MAX. CAM. WT.: 60 LBS.
INSTALL TIME: 30 MIN.



FAA - STC approved for *Bell* Jet Ranger / Long Ranger & *Eurocopter* Astar / TwinStar helicopters.



Tyler Camera Systems 14218 Aetna Street Van Nuys, California 91401 • USA
www.tylermount.com • 800-390-6070 • (818) 989-4420 • FAX (818) 989-0423



MIDDLE MOUNT II

GENERAL INFO

Optimized for mid-range size / weight cameras and lenses, the Middle Mount II shoots from right or left side, and provides 100 degrees of pan, tilt and roll; great for air-to-ground or air-to-air, and fast action sequences. Straight-forward or straight-back shots can be made by crabbing the helicopter; up to @ 40 mph. And, with Gyro Assist, the Middle Mount II achieves greater focal lengths with the same ease of operating. Your Operator, your AC, and your camera package.

OPTIMUM CAMERA TYPES

35 & 16MM CAMERAS: *Arriflex* 435, 235, 35-3, 416, 16SR 3 or 2, & Panavision
VIDEO CAMERAS: *Arriflex* D-20, and all broadcast hand-held type.

ADDITIONAL FEATURES

- No charge for prep (during business hours).
- Direct, through the eyepiece viewing for optimum focusing and framing.
- Quick in-flight magazine/video tape and filter changes.
- Controls for smooth, slow to high speed zooming, focus and camera run.

Note: Camera run function operates *Arriflex* type film cameras as well as most video cameras.

RENTAL RATES

<u>EQUIPMENT</u>	<u>DAILY</u>	<u>WEEKLY</u>
MIDDLE MOUNT & (1) BATTERY	@ \$ 620	@ \$ 2,480
with GYRO ASSIST & (1) BATTERY	965	3,860
add BATTERIES (EA.)	35	140
add SHIP POWER ADAPTER	25	100

INSURANCE VALUES

MIDDLE MOUNT @ \$ 125,000 - 140,000